

SIRIUS HRI 280 W RO

SIRIUS HRI | High-pressure discharge lamps with reflector



Areas of application

- Concert lighting
- Club and disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product family benefits

- Lightweight and compact reflector lamps
- Perfectly suited for small and lightweight moving heads
- Optimized burner design allows any burning position
- High luminance through very short arc and high pressure
- Bright light for brilliant light effects
- Long lifetime
- Easy lamp replacement
- Stable light output over the entire lifetime



Product datasheet

Technical data

Electrical data

Nominal wattage	280.00 W
Nominal current	4 A
Nominal voltage	70.0 V

Photometrical data

Nominal luminous flux	11500 lm
Color temperature	7800 K
Color rendering index Ra	78

Dimensions & weight

Diameter	51.0 mm
Length	54.5 mm
Arc length	0.9 mm

Lifespan

Lifespan	2000 h
----------	--------

Additional product data

Category	CUSTOMIZED
----------	------------

Capabilities

Burning position	Any
Working distance	34.5 mm

Certificates & standards

EEL – Energy Label	A
--------------------	---

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899082151 4052899110397
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SIRIUS HRI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899082151	SIRIUS HRI 280 W RO	Unpacked 1	55 mm x 51 mm x 51 mm	0.14 dm ³	60.00 g
4052899082168	SIRIUS HRI 280 W RO	Shipping carton box 60	595 mm x 400 mm x 186 mm	44.27 dm ³	5600.00 g
4052899110397	SIRIUS HRI 280 W RO	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm ³	113.00 g
4052899110403	SIRIUS HRI 280 W RO	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm ³	272.00 g
4052899110410	SIRIUS HRI 280 W RO	Shipping carton box 20	507 mm x 203 mm x 264 mm	27.17 dm ³	3201.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
