

XENARC ORIGINAL D5S

Four-year guarantee



The original spare parts with four-year guarantee

XENARC ORIGINAL lamps impress with a wide product range and the reliable OEM quality. Successfully used in millions of new automobiles from renowned manufacturers, whether as standard initial equipment or original spare parts. With up to 4,500 Kelvin color temperature, their light is closer to natural daylight than conventional halogen light with 3,200 Kelvin – and is thus more pleasant for the eyes. Thanks to the impressive intensity of the light, the lamps provide better visibility on the road. The durable lamps function as original spare parts of your vehicle and convince with their long lifetime. OSRAM provides a 4-year-guarantee for XENARC ORIGINAL lamps. Please note: XENARC lamp change is recommended to be carried out by a professional.

Product datasheet

Technical data


Electrical data

| | |
|-----------------|---------|
| Power input | 31 W |
| Nominal voltage | 12.0 V |
| Nominal wattage | 25.00 W |
| Test voltage | 13.5 V |

Photometrical data

| | |
|-------------------------|--------------|
| Luminous flux | 2000 lm |
| Luminous flux tolerance | +15 %; -10 % |
| Color temperature | 4400 K |

Dimensions & weight



| | |
|----------------|----------|
| Diameter | 9 mm |
| Product weight | 105.00 g |
| Length | 80.0 mm |

Lifespan

| | |
|-------------|---------|
| Lifespan B3 | 2500 h |
| Lifespan Tc | 4000 h |
| Guarantee | 4 years |

Additional product data

| | |
|-----------------------------|---------|
| Base (standard designation) | PK32d-7 |
|-----------------------------|---------|

Capabilities

| | |
|------------|-----|
| Technology | HID |
|------------|-----|

Product datasheet

Certificates & standards

| | |
|---------------------------|-------------------|
| ECE category | D5S ¹⁾ |
| Approval marks – approval | E4 approval |

¹⁾ To be operated only with approved electronic control gear

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---|--|
| Date of Declaration | 06-03-2024 |
| Primary Article Identifier | 4052899600522 4062172243483 4062172305457 4062172346771 |
| Candidate List Substance 1 | Lead |
| CAS No. of substance 1 | 7439-92-1 |
| Safe Use Instruction | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration No. in SCIP database | bcc5f4fd-71d7-4c7c-95ea-52ac3cd5a270 fe4e3ad5-b5ec-4b62-8d27-e4149a4ab5e1 |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4052899600522 | XENARC ORIGINAL D5S | Folding carton box 1 | 62 mm x 57 mm x 95 mm | 0.34 dm ³ | 131.00 g |
| 4062172095686 | XENARC ORIGINAL D5S | Shipping carton box 4 | 135 mm x 125 mm x 108 mm | 1.82 dm ³ | 576.00 g |
| 4062172095693 | XENARC ORIGINAL D5S | Shipping carton box 64 | 556 mm x 266 mm x 229 mm | 33.87 dm ³ | 9525.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Product datasheet



OSRAM