

# LEDDriving SL P21/5W WHITE

Ideal replacement for any vehicle



**Suitable for various vehicle exterior applications**

Available in Cool White



**Replaces conventional P21/5W lamps**

Easy upgrade to LED technology with plug & play solutions



**Reliable OSRAM quality stands for less lamp replacements**

4-year OSRAM guarantee (refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions)



### Suitable LED replacement for P21/5W

LEDDriving SL P21/5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

# Product datasheet

## Technical data

### Product information

Order reference	7528DWP
Product type (off-road vs. on-road)	Off-road $\pm$ P21/5W
Application (Category and Product specific)	Mainly used for signal/ indicator applications


### Electrical data

Power input	2.50 / 0.5 W
Nominal voltage	12.0 V
Nominal wattage	2.00/0.40 W
Power input tolerance	$\pm$ 25 %
Test voltage	13.5 V

### Photometrical data

Color temperature	6000 K
Luminous flux	145/30 lm
Luminous flux tolerance	$\pm$ 15 %
Light color LED	Cool white

### Dimensions & weight



Length	52.5 mm
Diameter	27.0 mm
Product weight	16.00 g

### Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

## Product datasheet

### Additional product data

Base (standard designation)	BAY15d
-----------------------------	--------

### Capabilities

Technology	LED <sup>1)</sup>
------------	-------------------

<sup>1)</sup> Light-emitting diode lamp

### Country specific categorizations

Order reference	7528DWP
-----------------	---------

### Environmental information


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	09-02-2024
Primary Article Identifier	4062172151726   4062172401197
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	026eb835-3aa5-4bfa-a635-bb4b42c468ab

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172151726	LEDiving SL $\triangleq$ P21/5W	Blister 2	135 mm x 95 mm x 18 mm	0.23 dm <sup>3</sup>	44.00 g
4062172151733	LEDiving SL $\triangleq$ P21/5W	Shipping carton box 10	119 mm x 109 mm x 151 mm	1.96 dm <sup>3</sup>	256.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 Brochures LEDiving Retrofits - Exchange overview (EN)

### Safety advice

## Product datasheet

Canbus compatible

Coloured lamps for usage behind coloured glass

### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.