

# LEDDriving SL W21W YELLOW

Ideal replacement for any vehicle



**Suitable for various vehicle exterior applications**

Available in Amber



**Replaces conventional W21W lamps**

Easy upgrade to LED technology with plug & play solutions



**Reliable OSRAM quality stands for less lamp replacements**

4-year OSRAM guarantee (refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions)



### Suitable LED replacement for W21W

LEDDriving SL W21W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional W21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

# Product datasheet

## Technical data

### Product information

Order reference	7505DYP
Product type (off-road vs. on-road)	Off-road $\pm$ W21W
Application (Category and Product specific)	Mainly used for signal/ indicator applications


### Electrical data

Power input	2 W
Nominal voltage	12.0 V
Nominal wattage	1.40 W
Power input tolerance	$\pm 10$ %
Test voltage	13.5 V

### Photometrical data

Luminous flux	55 lm
Luminous flux tolerance	$\pm 25$ %
Light color LED	Yellow

### Dimensions & weight



Length	47.5 mm
Diameter	20.0 mm
Product weight	12.00 g

### Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

## Product datasheet

### Additional product data

Base (standard designation)	W3x16d
-----------------------------	--------

### Capabilities

Technology	LED <sup>1)</sup>
------------	-------------------

<sup>1)</sup> Light-emitting diode lamp

### Country specific categorizations

Order reference	7505DYP
-----------------	---------

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	09-02-2024
Primary Article Identifier	4062172149273   4062172401593
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	242dbb41-1832-44be-a6e6-faceaa8bb4e0

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172149273	LEDiving SL $\triangleq$ W21W	Blister 2	135 mm x 95 mm x 18 mm	0.23 dm <sup>3</sup>	36.00 g
4062172149280	LEDiving SL $\triangleq$ W21W	Shipping carton box 10	119 mm x 109 mm x 151 mm	1.96 dm <sup>3</sup>	215.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 Brochures LEDiving Retrofits - Exchange overview (EN)

### Safety advice

## Product datasheet

Canbus compatible

Coloured lamps for usage behind coloured glass

### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.