

# TYREinflate 450



### Rapid Inflation Time

Inflate the tire to the desired pressure in ca. 3.5 minutes\*\*



### Wind-up Cable

Winding/unwinding mechanism for a neatly rolled up cable



### LED Light

Easy to operate even in darkness and in low light conditions



### Rapid tyre inflator with wind-up cable

The OSRAM Tyreinflate 450 can inflate a tyre from flat in 3.5 minutes\*\*. Comes with auto stop feature to accurately get the desired pressure for your tyre. Includes a backlit digital display and white LED light for optimal illumination in darkness. The Tyreinflate 450's flat, solid design makes the unit stable whilst in use, as well as the wind up cable eliminating any messy wires and helping you get back on the road faster. Comes complete with three piece adaptor kit for bicycle tyres, balls and other inflatables.\*\*based on inflating a 13" tyre from flat to 2.41 BAR

## Product family datasheet

### Technical data






Product description	Electrical data	Dimensions & weight			Additional product data	Capabilities
	Nominal voltage	Height	Width	Length	Display Type	Fuse
TYRE inflate 450	11.1 V	180.0 mm	88.0 mm	197.0 mm	Digital	10 A

Product description	Country specific categorizations	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	Order reference	Date of Declaration	Primary Article Identifier	Candidate List Substance 1
TYRE inflate 450	OTI450	07-03-2024	4052899620216	Lead

Product description	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
TYRE inflate 450	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	dda41c6e-d521-4522-a227-e170d9cf4d66

## Product family datasheet

### Download Data

File	
	User instruction TYREinflate 450
	Product movie TyreInflate How to Video (EN)
	Product movie TyreInflate 450 Product Video (EN)
	Video OSRAM TYREinflate 450: Rapid tyre inflator with wind-up cable, LED light and digital display
	Video OSRAM TYREinflate How To: Change your vehicle's tyre pressure easily

#### Safety advice

Product won't exceed noise levels of more than 90 dB

#### Legal advice

CE and EAC compliant

\* for precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

\*\* based on inflating a 13" tyre from flat to 2.41 BAR

Application advice:

For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.