

LEDinspect RECHARGEABLE UNDERBONNET LIGHT



Rechargeable

Up to 4.5h operating time.
Rechargeable via USB-C port
with a charging time of only
approx. 3 hours




Up to 1200lm (high) & 600lm (low)

Two light functions: Up to
1200lm (high) & 600lm (low)



Extendable

Extendable up to 1.8m. Fits
almost every underbonnet.



2-year OSRAM Guarantee*

Systematic quality assurance
measures underpin the
premium workmanship and
functionality of our products.
Innovative technology and
excellent quality really pay
dividends for our customers.

Product family datasheet



Light is versatile

This rechargeable underbonnet light from OSRAM is perfect for professional and private use. With two light functions up to 1200lm (high), 600lm (low) and a light bar that can be rotated up to 360°, this lighting fixture offers different adjustment options for a variety of tasks. The LEDinspect Rechargeable Underbonnet Light is particularly impressive with its great flexibility - it can be extended to a length of up to 1.80m and can therefore provide optimum lighting in the engine compartment in a wide range of vehicles. The rechargeable battery allows up to 2h operating time at high power or up to 4.5h at low power and with a charging time of only approx. 3 hours, this OSRAM lamp is also quickly ready for use again. A USB-C charging cable with 1.2m length for charging the lithium battery is included. In accordance with protection class IP65, this lamp has protection against the ingress of dust particles and against splashing water and is tested for impact resistance in accordance with IK07. With a weight of only 840g and soft pads at both ends of the mounting bar, this light bar is designed not to cause damage to the bonnet when used as instructed and is therefore ideal in professional workshops to be mounted on the bonnets of a wide range of vehicles from small to large. OSRAM also provides a 2-year guarantee**For precise conditions please refer to: www.osram.com/am-guarantee

Product family datasheet

Technical data

Product description	Product information		Electrical data		Photometrical data	
	Order reference	Application (Category and Product specific)	Nominal voltage	Nominal wattage	Light color LED	Luminous flux
INSPECTION LAMP	LEDIL415	LED inspection lights	3.7 V	16.28 W	White	1200 lm

Product description	Color temperature	LED module information	Dimensions & weight			
		Number of LEDs per module	Product weight	Height	Width	Length
INSPECTION LAMP	6500 K	32	840.00 g	67 mm	80 mm	1153 mm

Product description	Colors & materials	Lifespan	Additional product data	
	Base color	Guarantee	Type of Battery	Scope of battery
INSPECTION LAMP	Black / Orange	2 years	Rechargeable	Yes

Product description	Number of included batteries	Capabilities	Certificates & standards	Environmental information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Technology	IK Class	Date of Declaration
INSPECTION LAMP	1	LED	IK07	08-03-2024

Product description	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction
INSPECTION LAMP	4052899631021	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Product description	Declaration No. in SCIP database
INSPECTION LAMP	1f064e13-454b-4c4f-a3e5-26f8d1388215

Product family datasheet

Download Data

File	
	User instruction LEDinspect RECHARGEABLE UNDERBONNET LIGHT LEDIL415

Legal advice

Application advice: For more detailed application information and graphics please see product datasheet and the user instruction.

*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.