

LEDDriving HL BRIGHT HB3/H10/HIR1



Up to +300% more brightness

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner. Compared to minimum ECE R112, for H7/H18 & H4/H19



Very compact LED replacement for conventional HB3/H10/HIR1 high and low beam lamps

Reduced glaring thanks to an optimized light distribution



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



4 year OSRAM guarantee

For precise conditions, please refer to www.osram.com/am-guarantee



High-performing LED retrofit lamp providing improved visibility and a stylish look

With up to +300% more brightness (compared to ECE R112, for H7/H18 & H4/H19), the OSRAM LEDDriving HL BRIGHT retrofit lamp ensures optimum visibility and thus allowing drivers to recognize signs, obstacles and hazards sooner than conventional lamps. This LED retrofit lamp not only creates a stylish modern look with a cool white color temperature of 6,000K but also offers reduced glaring thanks to an optimized light distribution. Premium OSRAM quality and LED technology grant up to 5 times more lifetime (compared to ECE R112) and better visibility thanks to daylight effect. The pair of lamps comes with a 4-year OSRAM guarantee. For precise guarantee conditions please refer to www.osram.com/am-guarantee. The LEDDriving HL BRIGHT high and low beam lamps by OSRAM replace conventional halogen lamps and are 12V compatible. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description | Product information | | General Product Information | | Electrical Data |
|---|--|-------------------------------------|-----------------------------|--------------------|-----------------|
| | Application (Category and Product specific) | Product type (off-road vs. on-road) | Global order reference | Order denomination | Power input |
| LEDriving HL BRIGHT \triangleq HB3/H10/HIR1 | Mainly used for Low Beam, High Beam and Fog light applications | Off-road \triangleq HB3/H10/HIR1 | 9005DWBRT | 9005DWBRT-2HFB | 19 W |



| Product description | Nominal voltage | Nominal wattage | Photometric Data | | Physical Attributes & Dimensions |
|---|-----------------|-----------------|-----------------------|-------------------------|----------------------------------|
| | | | Nominal luminous flux | Luminous flux tolerance | Diameter |
| LEDriving HL BRIGHT \triangleq HB3/H10/HIR1 | 12.0 V | 19 W | 1900 lm | $\pm 20\%$ | 14.0 mm |

| Product description | Lifetime Data | Capabilities | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---|---------------|--------------|--|----------------------------|
| | Lifespan Tc | Technology | Date of declaration | Primary article identifier |
| LEDriving HL BRIGHT \triangleq HB3/H10/HIR1 | 5000 hr | LED | 22-09-2024 | 4062172315975 |

| Product description | Declaration no. in SCIP database |
|---|----------------------------------|
| LEDriving HL BRIGHT \triangleq HB3/H10/HIR1 | In work |

Product family datasheet

Download Data

| File | |
|---|---|
|  | User instruction LEDriving HL BRIGHT |
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

