Product family datasheet

## **OSRAM**

# NIGHT BREAKER H4-LED

OSRAM's first NIGHT BREAKER H4 LED for motorcycles





Street-Legal1)

The NIGHT BREAKER LED family - OSRAM's first streetlegal1) LED retrofit lamps.



Up to 230% more brightness2) & 6000K See and be seen with

OSRAM. Cool white color temperature similar to daylight. For more safety on the road, especially when driving at night



Up to 5 times longer lifetime3) Vibration resistant, environmentally friendly, and cost-efficient



4 year OSRAM guarantee

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



# With the NIGHT BREAKER H4 LED for Motorcycles, OSRAM's first street legal1) H4-LED replacement lamp for Motorcycles is now on the market

With the street-legal1) NIGHT BREAKER H4-LED you can now upgrade the function of your high- and low beam lights of your motorcycle to state-of-the-art LED technology. These LED replacement lamps are suitable as a replacement for conventional H4 lamps and bases. They offer a modern and bright white light with a color temperature of up to 6000 Kelvin and impress with up to 230% more brightness2), while the glare of other road users falls below the permissible maximum values by up to 50%2). In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 55% less energy and convince thanks to the LED technology and the specially developed vibrationresistant design, with up to 5 times longer life time3). You can now replace your motorcycle lamps with OSRAM's revolutionary NIGHT BREAKER LED retrofit lamps and experience trend-setting brightness with road approval1) Additionally, OSRAM offers a dedicated guarantee on all NIGHT BREAKER LED retrofit lamps2)

### Product family datasheet

### Technical data

	Product in	formation						
Product description	Product le 1	gal advice	Product legal ad 2	vice Product lega	Product legal advice 3		Application (Category and Product specific)	
NIGHT BREAKER H4 LED	light source applies to respective in which th approval of an equival approval a the vehicle and light f currently L compatibil more deta	1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb- led			3) Compared to halogen lamps		High and low beam	
	General Pr Informatio		Electrical Data					
Product description	Global ord reference	Global order reference		Nominal wa	Nominal wattage		Test voltage	
NIGHT BREAKER H4 LED	64193DWI	NB	12.0 V	27 W		±15 %	13.2 V	
		Photometric Data			Physical Attrib Dimensions			
Product description	Power input	Light color LED	Nominal luminous Color temperature flux		Diameter			
NIGHT BREAKER H4 LED	27/23 W	Cool white	1650/1000 ln	n 6000 K		18.5 m	m	
						Lifetime D	ata	
Product description	Lamp base	2	Length	Product wei	Product weight		Lifespan B3	
NIGHT BREAKER H4 LED	P43t		87.4 mm	80.00 g		2500 hr	1500 hr	
	Capabilitie	Capabilities Certific standa		Information accordin	onmental & Regulatory Info nation according Art. 33 of ation (EC) 1907/2006 (REA			
Product description	Technolog	y Standa		Primary article identifier	Declaration no. in SCIP database			
		-		4062172382632	In work		-	

### Product family datasheet

#### Download Data

	File
1	Brochures LEDriving Retrofits - Exchange overview (EN)
	ref_pim_amsp_product360degreeimages NIGHT BREAKER LED H4-LED 64193DWNB-2HFB

#### Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

#### Legal advice

1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led

2) Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 50%

3) In comparison to traditional Halogen lamps

4) For precise conditions please refer to: www.osram.com/am-guarantee

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

