# **OSRAM**

## NIGHT BREAKER H1-LED

### OSRAM's first NIGHT BREAKER H1 LED



Street-Legal1)

The NIGHT BREAKER LED family - OSRAM's first street-legal1) LED retrofit lamps.



6000K & Cool White

See and be seen with OSRAM. Cool white color temperature similar to daylight. For more safety on the road, especially when driving at night



# Up to 5 times longer lifetime3)

Vibration resistant, environmentally friendly, and cost-efficient



### 4 year OSRAM guarantee

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



## With the NIGHT BREAKER H1 LED OSRAM's first street legal1) H1-LED replacement lamp is now on the market

With the street-legal1) NIGHT BREAKER H1-LED you can now upgrade the function of your high- and low beam lights of your vehicle to state-of-the-art LED technology. These LED replacement lamps are suitable as a replacement for conventional H1 lamps and bases. They offer a modern and bright white light with a color temperature of up to 6000 Kelvin and impress with reduced glare for other road users that is up to 40% lower as the permissible maximum values2). In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 55% less energy and convince thanks to the LED technology and the specially developed vibration-resistant design, with up to 5 times longer life time3). You can now replace your vehicle lamps with OSRAM's revolutionary NIGHT BREAKER LED retrofit lamps and experience trend-setting brightness with road approval1) Additionally, OSRAM offers a dedicated guarantee on all NIGHT BREAKER LED retrofit lamps2)

## Product family datasheet

## Technical data

|                      | Product information  |   |                             |  |  |   |         |  |  |
|----------------------|--|---|-----------------------------|--|--|---|---------|--|--|
| Product description  | Product le   | Product legal advice  |                             | Product legal advice<br>2  |  | Product legal advice<br>3                       |         | Application (Category and Product specific)    |  |
| NIGHT BREAKER H1 LED | light source<br>applies to<br>respective<br>in which t<br>approval of<br>approval a<br>the vehicle<br>and light for<br>currently logomered | 1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb- |                             | 2) In comparison to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 40% |  |   |         | High and low beam                              |  |
|                      | General Product<br>Information   |   | Electrical Data             |  |  |   |         |  |  |
| Product description  | Global order<br>reference  |   | Power Nominal voltage input |  | -  | Power Nominal wattage<br>input<br>toleranc<br>e |         |  |  |
| NIGHT BREAKER H1 LED | 64150DWNB  |   | 16.0 W                      | 12.0 V   | ±15 %  |   | 16 W    |  |  |
|                      | Photometric Data   |   |                             |  |  |   |         | Physical<br>Attribut<br>es &<br>Dimensi<br>ons |  |
| Product description  | Color tem  | Color temperature   |                             | Nominal luminous<br>flux   |  | or Luminous<br>flux<br>tolerance                |         | Lamp<br>base                                   |  |
| NIGHT BREAKER H1 LED | 6000 K   |   | 1550 lm                     |  | Cool white   | ±15 %   |         | P14.5s   |  |
|                      |  |   |                             |  |  |   | Lifetin | ne Data  |  |
| Product description  | Diameter   | Diameter  |                             | Product weight   |  | Length  |         | Lifespan Tc                                    |  |
| NIGHT BREAKER H1 LED | 11.8 mm  | 11.8 mm   |                             | 50.00 g  |  | 76.2 mm   |         | 2500 hr  |  |
|                      | Capabiliti   |   | s Certificates & standards  |  | Environmental & Re<br>Information accordi<br>Regulation (EC) 190 |   | -       |  |  |
| Product description  | Lifespan   | Lifespan Technology<br>B3   |                             | Standards  |  | Primary article identifier                      |         | Declaration no. in SCIP database               |  |
|                      | В3   |   |                             |  | identifie  | r   | SC      | P database                                     |  |

## Product family datasheet

#### **Download Data**

#### File



User instruction

NIGHT BREAKER LED H1 64150DWNB



**Brochures** 

LEDriving Retrofits - Exchange overview (EN)

### Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

### Legal advice

- 1) Approved LED light source only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led
- 2) Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 40%
- 3) In comparison to traditional Halogen lamps
- 4) For precise conditions please refer to: www.osram.com/am-guarantee

### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

