# **OSRAM**

# TRUCKSTAR LED H7

OSRAM's first TRUCKSTAR H7 LED for 24-volt vehicles





Street-Legal 1)

The TRUCKSTAR LED -OSRAM's first street-legal1) LED retrofit lamps for 24V Vehicles.



# Up to 230% more brightness2) & 6000K

See and be seen with OSRAM. Cool white color temperature similar to daylight. For more safety on the road, especially when driving at night



#### **Heavy Duty Application**

Specially developed vibration-resistant design, engineered for the 24V and "heavy duty" range for an up to 5 times longer lifetime3)



#### 4 Year OSRAM Guarantee4)

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

## Product family datasheet



# With the TRUCKSTAR H7 LED, OSRAM's first street-legal1) H7 LED retrofit lamp for 24V vehicles is now on the market.

For truck drivers, fleet managers and freight forwarders. For trucks, special vehicles, buses, and towing vehicles. For nearly everyone in the "heavy duty" sector and beyond. With the street-legal1) TRUCKSTAR H7-LED for 24V Vehicles you can now upgrade the function of your high- and low beam lights of your vehicle to state-of-the-art LED technology. These LED replacement lamps are suitable as a replacement for conventional H7 lamps and bases. They offer a modern and bright white light with a color temperature of up to 6000 Kelvin and impress with up to 230% more brightness2), while the glare of other road users falls below the permissible maximum values by up to 50%2). In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 75% less energy and convince thanks to the LED technology and the especially developed and vibrationresistant design, engineered for the 24V and "heavy duty" range, with up to 5 times longer life time3). You can now replace your vehicle lamps with OSRAM's revolutionary retrofit lamps and experience trend-setting brightness with road approval1) Additionally, OSRAM offers a dedicated guarantee on all TRUCKSTAR LED retrofit lamps4)

# Product family datasheet

### Technical data

	Product inf	formation						
Product description	Product leg	Product legal advice			Product legal advice 3		Application (Category and Product specific)	
TRUCKSTAR H7 LED			2) In comparison the minimum requirements of R112, while the is below the maximum permissible valup to 50%	f ECE e glare	3) In compariso traditional Halo lamps		High and I	low beam
	General Pr		Electrical Data					
Product description	Global ordereference	Global order reference		e	Nominal wattage		Power input toleranc e	Test voltage
TRUCKSTAR H7 LED	64215DWT	-S	24.0 V		16 W		±10 %	28.0 V
		Photometri	c Data					
Product description	Power input	Light color LED	Luminous flux tolerance	Nominal luminous flux		Colo	Color temperature	
TRUCKSTAR H7 LED	16.0 W	Cool white	±10 %	1500	lm	6000	ЭК	
	Physical At	tributes & D	imensions				Lifetime D	)ata
Product description	Lamp base	Lamp base			Product weight		Lifespan Tc	Lifespan B3
TRUCKSTAR H7 LED	PX26d		77.9 mm		60.00 g		2500 hr	1500 hr
	Capabilitie	Capabilities Certification standar		Informat	ovironmental & Regulatory Info formation according Art. 33 of I gulation (EC) 1907/2006 (REA		EU	
Product description	Technolog	Technology Standar		Primary a				
TRUCKSTAR H7 LED	LED	ABG		4042472	384919	In work		

# Product family datasheet

#### **Download Data**

	File
7	User instruction TRUCKSTAR LED H7 LED 24V 64215DWTS
<b>大</b>	Brochures LEDriving Retrofits - Exchange overview (EN)
<u>Z</u>	Brochures TRUCKSTAR LED Compatibility List Trucks (EN)

### Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

#### Legal advice

- 1) Approved LED light source only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led
- 2) Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 50%
- 3) In comparison to traditional Halogen lamps
- 4) For precise conditions please refer to: www.osram.com/am-guarantee

### **Application advice**

For more detailed application information and graphics please see product datasheet.

### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

