OSRAM

Flush mount WL VX100-FL



Flood Beam Pattern

For a wide and broad light distribution



Up to 45 m long beam

See and be seen with OSRAM



Robust and vibration resistant

Specially designed for demanding work environments and rough offroad terrain



IP & IK protection classes

Tested and validated in a DINcertified environmental simulation laboratory regarding extreme external influences

Product family datasheet





Powerful LED working lights

Discover the versatility of the OSRAM LEDriving Flush Mount WL VX100-FL for powerful near-field and far-field illumination at the front, rear or side of your vehicle. The working light combines affordability with exceptional performance, quality and functionality. With a luminous flux of up to 600lm and a flood beam pattern with a wide and broad light distribution, the working light is ideal for illuminating near- and far-field areas, such as campsites, work areas or construction sites. Thanks to the lightweight rugged construction and sleek shape, the working light seamlessly integrates into the vehicle's design, offering enhanced visibility without compromising on style. With a light beam reaching up to 45 meters and a light color of 6500 Kelvin, it ensures clear visibility even in the darkest conditions. The working light is compatible with both 12V and 24V electrical systems, making them suitable for a wide range of vehicles including trucks, agricultural machinery, construction vehicles, caravans, quads and off-road vehicles1). Whether for demanding work environments, camping trips or off-road adventures, the LED Flush Mount offers versatile lighting solutions tailored to various driving scenarios. Equipped with a shatterproof polycarbonate lens and aluminum die-cast housing, the LEDriving Flush Mount WL VX100-FL is robust and vibration resistant to withstand the harshest conditions. It has been tested and validated with the highest IP-Protection Classes IP6K8 & IP6K9K in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. In addition, OSRAM provides a 2-year guarantee on the product2).1) Additional working lights without ECE approval for use as work lights are approved for use on any vehicle according to German Road Traffic Licensing Regulations (StVZO) §52 (7). However, they must not be used and switched on while driving. In addition, individual special regulations, and laws of countries outside Germany must be observed.2) For precise conditions refer to: www.osram.com/am-quarantee

Product family datasheet

Technical data

	Product information	General Product Information		Electrical Data	
Product description	Application (Category and Product specific)	Global order reference		Nominal voltage	Nominal wattage
Flush Mount WL VX100-FL 1)	Working light application	LEDFLUSH101-FL 12/24 V 6 W			
	Photometric Data	LED module information	Lifetii Data	me Capabilities	Certificates & standards
Product description	Nominal luminous flux	Number of LEDs per module	Lifesp Tc	an Technology	Type of protection
Flush Mount WL VX100-FL 1)	600 lm	2	5000	hr LED ²⁾	IP6K8/IP6K9K
		Logistical data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REAC))
Product description	Standards	Commodity code		Declaration no. in SCIP database	
Flush Mount WL VX100-FL 1)	ECE R10	85122000900		In work	

 $^{^{1)}}$ Beam Pattern: Flood

 $^{^{2)}}$ Light-emitting diode application

Product family datasheet

Download Data

	File
大	User instruction LEDriving Flush Mount WL VX100-FL LEDFLUSH101-FL
D	Movie application LEDriving D and W Image Video Bringing light to life (EN)
D	Movie application LEDriving Driving and Working Lights Reference Video (EN)
D	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
D	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)

Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

Legal advice

2) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.